



HWF - 4916X

SPECIFICATIONS

Capacity:	66,000 Gallons
Flow Rate:	7.5 GPM
Micron Rating:	10.2 Micron
Operating Pressure:	20-125 PSI
Operating Temperature:	35°-100° F

Note: Use and filter capacity vary by the individual filter only. For systems containing multiple filters, refer to your installation manual for specifications.

Note: For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities. For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities. For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities.

Check for clogging with open end of filter and replace. Do not use with water that is contaminated with oil or grease. Do not use with water that is contaminated with oil or grease. Do not use with water that is contaminated with oil or grease.

For more information on the benefits of this filter, visit our website at www.home-water-filter.com.

To be serviced by an authorized licensed plumbing professional only.

BECAUSE PEOPLE MATTER™

AQUAMOR

The Home Water Filter Company

P.O. Box 2300 • Hayward, CA 94520

Telephone: (510) 342-5224

www.home-water-filter.com

PHW10074 (EPA Est. No. 92705)



57787-00870

Units Included

HWF - 4923PHC

Sediment, Chlorine & Cyst Reduction Plus Hard Water Solution

SPECIFICATIONS

Capacity:	265,000 Gallons
Flow Rate:	7.5 GPM
Micron Rating:	0.2 Micron
Operating Pressure:	20-80 PSI
Operating Temperature:	35°-150° F

Note: Use and filter capacity vary by the individual filter only. For systems containing multiple filters, refer to your installation manual for specifications.

Note: For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities. For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities.

Check for clogging with open end of filter and replace. Do not use with water that is contaminated with oil or grease. Do not use with water that is contaminated with oil or grease.

For more information on the benefits of this filter, visit our website at www.home-water-filter.com.

To be serviced by an authorized licensed plumbing professional only.

BECAUSE PEOPLE MATTER™

AQUAMOR

The Home Water Filter Company

P.O. Box 2300 • Hayward, CA 94520

Telephone: (510) 342-5224

www.home-water-filter.com

PHW10074 (EPA Est. No. 92705)



57787-00870

Units Included

HWF - 4923PHC

Sediment, Chlorine & Cyst Reduction Plus Hard Water Solution

SPECIFICATIONS

Capacity:	265,000 Gallons
Flow Rate:	7.5 GPM
Micron Rating:	0.2 Micron
Operating Pressure:	20-80 PSI
Operating Temperature:	35°-150° F

Note: Use and filter capacity vary by the individual filter only. For systems containing multiple filters, refer to your installation manual for specifications.

Note: For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities. For cartridge every 1 month to ensure proper filter performance and continued reduction of the listed impurities.

Check for clogging with open end of filter and replace. Do not use with water that is contaminated with oil or grease. Do not use with water that is contaminated with oil or grease.

For more information on the benefits of this filter, visit our website at www.home-water-filter.com.

To be serviced by an authorized licensed plumbing professional only.

BECAUSE PEOPLE MATTER™

AQUAMOR

The Home Water Filter Company

P.O. Box 2300 • Hayward, CA 94520

Telephone: (510) 342-5224

www.home-water-filter.com

PHW10074 (EPA Est. No. 92705)



57787-00870

Units Included

040592019 0120005