

TITANIUM - CHLORINE

HWF - 2423X

Sediment, Chlorine & Cyst Reduction

SPECIFICATIONS

Capacity:	55,000 Gallons
Flow Rate:	3.0 GPM
Micron Rating:	0.2 Micron
Operating Pressure:	30-80 PSI
Operating Temperature:	35°-130° F



**Scan For
Owner's Manual**

Flow rate and filter capacity refer to the individual filter only. For systems containing multiple filters, refer to the system installation manual for specifications.

The cartridge capacity may vary according to flow rate, inlet line pressure and local water conditions, which may require more frequent cartridge replacement.

Check for compliance with state and local laws and regulations. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. The contaminants or substances reduced by this filter are not necessarily in your water. For additional product information, please visit www.honestwaterfilter.com.

To be serviced by an authorized licensed plumbing professional only.



BECAUSE YOU MATTERSM

by **AQUAMOR**



Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of Cyst, Chlorine, Taste and Odor.

The Honest Water Filter Company

www.honestwaterfilter.com

P/N 902090 | EPA Est. No. 92705



Date Installed